


CSU 50AC & CSU 50RL



Cutter capacity
2" dia.



Lightweight, two-speed, high-performance drills

Powerful • Reliable

- Strong 10.5 Amp motor
- Compact, lightweight and portable – 16-1/2" high, 29 lbs.
- 2-gear variable speed gearbox
- Designed for continuous use

Drill up to 2" dia.

- Uses annular cutters up to 2" dia.; 5-1/4" stroke
- Twist drilling capacity up to 7/8" dia.
- Tapping capacity up to 15/16" dia.*
- Automatic lubrication system

Keyless Cutter Mount

- Easy "twist and lock" keyless arbor
- Also includes manual arbor for 3/4" Weldon shank (MT2) with set screws

REVERSIBLE

Model CSU 50RL has a variable-speed, reversible motor for tapping up to 15/16"

Optional quick-change tapping chuck with MT2 connection (Model GSW-222) has flexible collet to fit taps 5/16" to 5/8"



Integrated Safety

- SafeMag™ Green/Red LED magnetic force indicator for safe operation
- Equipped with CoolMag™ overheat protection
- Emergency-off function



With included geared chuck, these models easily convert to standard drill presses with a 4 1/2" stroke for conventional twist drills. Optional 3/4" geared chuck available (Part No. IBC 22).

CSU 50AC Specifications

Motor Power	10.5 Amp / 110 Volt
Weight	29 lbs.
Hole Capacity	2" dia.
Twist Drill Capacity	7/8" dia.
Tapping Capacity	15/16" (CSU 50RL only)
Speeds	1: 250 RPM, 2: 450 RPM
Magnet Base Size	6 1/2" L x 3 1/2" W
Dimensions	16 1/2" H x 9" L x 6 3/8" W
Magnetic Force (1" plate)	3750 lbs.
Arbor Bore	3/4" Weldon Shank
Spindle	MT2
Automatic Lubrication	Included
Reversible Motor	Order CSU 50RL
Power Assist	Order Accessory ZPA 401

* Model CSU 50RL for tapping up to 15/16" dia.



Tap collet set included with Model CSU 50RL

Standard Equipment includes auto lubrication, auto chuck cutter holder, manual chuck with set screws, geared chuck, safety chain, carabin hook, allen keys, pilot pins and carrying case. (CSU 50RL shown)

➤ *Annular Cutters: pages 36-46* ➤ *Accessories: pages 47-53*